



Product Overview

Average life (Nominal) (h)	15000
ETIM Class	EC001959
Product name	REFLED R80 V3 806LM 840 E27 SL
Product EAN number	5410288285221
Colour Consistency (SDCM)	6
Watt (Rated) (W)	9
Product Voltage (V)	230
Colour temperature (K)	4000
Light colour	Cool White
Colour Variation Initial (SDCM)	6
CRI (Ra)	80
General application	Hospitality, Residential & Consumer
Fixture rating	Open
Wattage (W)	9
Cap/Base	E27

Data table

GENERAL DATA

Product name	REFLED R80 V3 806LM 840 E27 SL
Watt (Rated) (W)	9
Cap/Base	E27
Fixture rating	Open

General application Hospitality, Residential & Consumer

ETIM Class EC001959

OPTICAL DATA

Rated Luminous Flux Useful (lm) 806

Colour temperature (K) 4000

Light colour Cool White

CRI (Ra) 80

Colour Consistency (SDCM) 6

Colour Variation Initial (SDCM) 6

Rated Luminous Intensity (cd) 198

Lumen maintenance at end of nominal life (%) 70

ELECTRICAL DATA

Wattage (W) 9

Equivalent watt (W) 60

Starting time (max) (s) 0.5

Warm-up time to 60% of full light (max) (s) 1

Product Voltage (V) 230

Lamp power factor 0.5

Control gear required No

No. Of switching cycles before premature failures 50000

Inrush Current (A) 2.4

Lamp Energy Label (class) A+

kWh per 1000 hours burning time 9

Nominal Frequency (Hz) 50/60Hz

Max. Luminaires per 10A C Breaker 3

Max. Luminaires per 16A C Breaker 5

Max. Luminaires per 20A C Breaker 7

LIFETIME DATA

Average life (Nominal) (h) 15000

Average life (Rated) (h) 15000

PHYSICAL DATA

Nominal Product Length (mm)	114
Nominal Product Diameter (mm)	81
Weight (kg)	0.15

PACKAGING

Single packaging type	Carton
Product EAN number	5410288285221
Packaging single length / height (cm)	4.5
Packaging single width (cm)	4.5
Packaging single depth (cm)	7.8
DUN14 (inner)	25410288285225
Units per inner package	6
DUN14 (outer)	15410288285228
Units per outer package	60
Packaging outer length / height (cm)	25.0
Packaging outer width (cm)	17.0
Packaging outer depth (cm)	12.5

SAFETY DATA

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

Energy label

