



LED Floodlight



OUTDOOR

POWER

Safe power solutions for garden and light DIY use

FEATURES

- Die-cast housing
- Sturdy steel bracket for simple installations
- Pre-wired 0.3m H05RN-F 3G1.0mm² cable
- IP68 connector

PRODUCT IMAGES



TECHNICAL SPECIFICATIONS

	Size	Wattage	Lumens
EFLDF10B40-M5	114mm x 52mm x 114mm	10W	800
EFLDF20B40-M5	129mm x 54mm x 121mm	20W	1600
EFLDF30B40-M5	144mm x 53mm x 132mm	30W	2400
EFLDF50B40-M5	184mm x 52mm x 165mm	50W	4000
EFLDF100B40-M5	285mm x 53mm x 283mm	100W	8000
EFLDF150B40-M5	400mm x 81.5mm x 382.5mm	150W	18000
EFLDF200B40-M5	400mm x 81.5mm x 382.5mm	200W	24000

CAT NO.	WEIGHT (g)	EFFICACY (Llm/W)	CRI	FREQUENCY (Hz)	IK RATING	TEMP RANGE	AMBIENT TEMP RATED LIFE (°C)	L/B RATED LIFE
EFLDF10B40	302	80	≥80	50	IK06	-20 to +45	25	70/50
EFLDF20B40	365	80	≥80	50	IK06	-20 to +45	25	70/50
EFLDF30B40	439	80	≥80	50	IK06	-20 to +45	25	70/50
EFLDF50B40	720	80	≥80	50	IK06	-20 to +45	25	70/50
EFLDF100B40	1549	80	≥80	50	IK06	-20 to +45	25	70/50
EFLDF150B40	4450	80	≥80	50	IK06	-20 to +45	25	70/50
EFLDF200B40	4465	80	≥80	50	IK06	-20 to +45	25	70/50

INSTALLATION INFORMATION

Installation Instructions

To comply with regulations, installation must be carried out by suitably qualified competent person and in accordance with the current IEE Wiring Regulations (BS7671) and Building Regulations. A copy of the instructions must be left for the user/Maintenance engineer for future reference.

Masterplug Help Line
0845 194 7584

Supplied by
Masterplug Ltd
Stafford Park 1 Telford TF3 3BD ENGLAND

Visit our website at
www.masterplug.com