

ToLEDo Candle

ToLEDo Candle FR 470LM 865 E14 SL

0026973



Range Features

-

PRODUCT OVERVIEW

Lamp finish	Frosted
Lamp shape	Candle
Colour temperature (K)	6500
CRI (Ra)	80
Dimmable	No
Energy class	A+
Equivalent watt (W)	40
Cap/Base	E14
Watt (Nominal) (W)	5.5
Light colour	Daylight
Ordering number	0026973
Efficacy (Rated) (lm/w)	85.45
Average life (Rated) (h)	15000
Luminous flux (Rated) (lm)	470
Technology	LED
Voltage (V)	220-240
Colour consistency (SDCM)	6

DATA TABLE

General data

Average life (Nominal) (h)	15000
Control gear required	No
Lamp finish	Frosted
Lamp shape	Candle
Dimmable	No
Dry applications use only	Yes
Energy class	A+
Energy saving lamp	Yes

ToLEDo Candle

ToLEDo Candle FR 470LM 865 E14 SL

0026973

General application	Hospitality; Residential & Consumer
Intended purpose	No
Cap/Base	E14
Lamp mercury content (mg)	0
No. of switching cycles before premature failure (min)	50000
Optimal operating condition (°C)	25
Ordering number	0026973
Product name	ToLEDo Candle FR 470LM 865 E14 SL
Average life (Rated) (h)	15000
Special purpose lamp	No
Starting time (max) (s)	0.05
Technology	LED
Transformer required	No
Warm-up time to 60% of full light (max) (s)	< 1s => 60%

Optical data

Colour temperature (K)	6500
CRI (Ra)	80
Light colour	Daylight
Lumen maintenance at end of nominal life (%)	70
Luminous flux (Nominal) (lm)	470
Luminous flux (Rated) (lm)	470
Suitable for accent lighting	No
Adjustable chromaticity	No
Colour consistency (SDCM)	6

Electrical data

Drive current (mA)	51
Equivalent watt (W)	40
kWh per 1000 hours burning time	6
Lamp power factor	0.5
Watt (Nominal) (W)	5.5
Efficacy (Rated) (lm/w)	85.45
Watt (Rated) (W)	5.5
Voltage (V)	220-240

Physical data

Max. Lamp Diameter (mm) - D	38
Lamp Length (mm) - C/L	110
Lamp dimension equal to filament lamp equivalent	Yes

ToLEDo Candle

ToLEDo Candle FR 470LM 865 E14 SL

0026973

TECHNICAL DRAWINGS

