

ToLEDo Ball Dimmable

ToLEDo Ball DIM FR 470LM 865 E14 SL

0026974



Range Features

-

PRODUCT OVERVIEW

Lamp finish	Frosted
Lamp shape	Ball
Colour temperature (K)	6500
CRI (Ra)	80
Dimmable	Yes
Energy class	A+
Equivalent watt (W)	40
Cap/Base	E14
Watt (Nominal) (W)	6.2
Light colour	Daylight
Ordering number	0026974
Efficacy (Rated) (lm/w)	75.80
Average life (Rated) (h)	25000
Luminous flux (Rated) (lm)	470
Technology	LED
Voltage (V)	220-240
Colour consistency (SDCM)	6

DATA TABLE

General data

Average life (Nominal) (h)	25000
Control gear required	No
Lamp finish	Frosted
Lamp shape	Ball
Dimmable	Yes
Dry applications use only	Yes
Energy class	A+
Energy saving lamp	Yes

ToLEDo Ball Dimmable

ToLEDo Ball DIM FR 470LM 865 E14 SL

0026974

General application	Hospitality; Residential & Consumer
Intended purpose	No
Cap/Base	E14
Lamp mercury content (mg)	0
No. of switching cycles before premature failure (min)	50000
Optimal operating condition (°C)	25
Ordering number	0026974
Product name	ToLEDo Ball DIM FR 470LM 865 E14 SL
Average life (Rated) (h)	25000
Special purpose lamp	No
Starting time (max) (s)	0.05
Technology	LED
Transformer required	No
Warm-up time to 60% of full light (max) (s)	< 1s => 60%

Optical data

Colour temperature (K)	6500
CRI (Ra)	80
Light colour	Daylight
Lumen maintenance at end of nominal life (%)	70
Luminous flux (Nominal) (lm)	470
Luminous flux (Rated) (lm)	470
Suitable for accent lighting	No
Adjustable chromaticity	No
Colour consistency (SDCM)	6

Electrical data

Drive current (mA)	45
Equivalent watt (W)	40
kWh per 1000 hours burning time	7
Lamp power factor	0.5
Watt (Nominal) (W)	6.2
Efficacy (Rated) (lm/w)	75.80
Watt (Rated) (W)	6.2
Voltage (V)	220-240

Physical data

Max. Lamp Diameter (mm) - D	45
Lamp Length (mm) - C/L	89
Lamp dimension equal to filament lamp equivalent	Yes

ToLEDo Ball Dimmable

ToLEDo Ball DIM FR 470LM 865 E14 SL

0026974

TECHNICAL DRAWINGS

